

microGradiparete

halogen energy saver

Halogen free standing, wall, ceiling and desk lamps for interiors. Consisting of a cylinder made of highly heat-resistant glass treated with special enamels, the lighting body takes care of the various different functions of reflector, antiglare shade and bulb protection in one piece. The reflector can be oriented through 360°. No tools are needed to replace the bulbs.



17
6 3/4"



11
4 3/8"



LUMINAIRE

materials	steel, zama, borosilicate glass
environment	interiors
mounting location	wall
emission	retinato: indirect light
	opalescente: diffused and indirect light
	tuttopalescente: diffused light
weight	0,3 kg
voltage	230V
insulation class	2
IP classification	IP20
marks	CE
design Franco Bettonica, Mario Melocchi, 1998	

LIGHT SOURCE

source	halogen energy saver
socket	R7s
ILCOS code	HDG74,9
bulb included	yes
number of bulbs	1
power	80W (max 100W)
life	2.000 h
energy label	C
luminous flux	1.520 lm
colour temperature	2.900 °K

FINISHES



shiny chrome
retinato
cod 508



shiny chrome
opalescente
cod 521



shiny chrome
tuttopalescente
cod 542



satin nickel-plated
retinato
cod 512



satin nickel-plated
opalescente
cod 522



satin nickel-plated
tuttopalescente
cod 543



satin chrome
retinato
cod 1508



satin chrome
opalescente
cod 1521



satin chrome
tuttopalescente
cod 1542

CINI & NILS